Food Wrapping Paper — Prime

Origin: EU · Food-contact grade · 100% thermomechanical pulp

PAPERMAT REF.
PM-FW-038/045



Designed for direct contact with dry, moist and fatty food and foodstuff. Manufactured from 100% thermomechanical pulp.

- Excellent paper for food packaging
- Fantastic in printing
- ISEGA certified product
- **Available from 38 gsm up to 45 gsm**

TYPICAL END USES

- **Protective food packaging and wrapping solutions**
- **Interleaving for food preparation and production lines**
- **Liner and fluting for corrugated products**

CERTIFICATES

Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
EU Ecolabel
FSC® certified
PEFC certified
ISEGA certified product

REEL SPECIFICATIONS

Reel width range: 310 – 2400 mm
Max reel diameter: 1250 mm
Max trimmed width: 8400 mm

TECHNICAL SPECIFICATIONS – target values

Substance	ISO 536	g/m^2	38**	40	42.5	45
Brightness	ISO 2470-1 (C/2°)	%	58	58	58	58
Opacity	ISO 2471	%	89	91	92	94
Thickness	ISO 534	µm	63	67	70	74
Smoothness	PPS 1MPa, ISO 8971-4	µm	3.9	3.9	3.9	3.9

** = Available depending on trim and ordered volumes

STORAGE AND HANDLING

- **The paper should be stored in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C – 23°C.**
- **If stored in a non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.**
- **Open the protective wrapping at the moment of use.**